

### ■ SURFACE MOUNTING - IP44

#### ADVANCE2 Series

560.



562.



567.



COMPACT  
WITHOUT FUSE HOLDER

COMPACT  
WITH FUSE HOLDER

LARGE  
WITH RAIL DIN (6 MODULES)

16A  
M25  
h 1/12

32A  
M25  
h 1/12

16A  
M25  
h 1/12

32A  
M25  
h 1/12

16A  
M25  
h 1/4

32A  
M25  
h 1/4

Poles	Hz.	Volt	Colour	h.	16A M25 h 1/12	32A M25 h 1/12	16A M25 h 1/12	32A M25 h 1/12
2P+E	50/60	100-130	Yellow	4	560.1670	560.3270	562.1670	562.3270
	50/60	200-250	Blue	6	560.1683	560.3283	562.1683	562.3283
	50/60	380-415	Red	9	560.1678	560.3278	562.1678	562.3278
	50/60	480-500	Grey	7	560.16836	560.32836	562.16836	562.32836
	50/60	trasf.	Grey	12	560.16833	560.32833	562.16833	562.32833
	>300-500	(1) >50	Green	2	560.16832	560.32832	562.16832	562.32832
	c.c.	(2) >50-250	Grey	3	560.16834	560.32834	562.16834	562.32834
	c.c.	(2) >250	Grey	8	560.16838	560.32838	562.16838	562.32838
3P+E	50/60	100-130	Yellow	4	560.1672	560.3272	562.1672	562.3272
	50/60	200-250	Blue	9	560.1674	560.3274	562.1674	562.3274
	50/60	380-415	Red	6	560.1686	560.3286	562.1686	562.3286
	60	440-460	Red	11	560.16865	560.32865	562.16865	562.32865
	50/60	480-500	Grey	7	560.16866	560.32866	562.16866	562.32866
	50/60	(3) 600-690	Black	5	560.16867	560.32867	562.16867	562.32867
	50/60	380/220	Red	3	560.16864	560.32864	562.16864	562.32864
	100-300	(1) >50	Green	10	560.16861	560.32861	562.16861	562.32861
>300-500	(1) >50	Green	2	560.16862	560.32862	562.16862	562.32862	
3P+N+E	50/60	100-130	Yellow	4	560.1679	560.3279	562.1679	562.3279
	50/60	208-250	Blue	9	560.1675	560.3275	562.1675	562.3275
	50/60	346-415	Red	6	560.1687	560.3287	562.1687	562.3287
	50/60	480-500	Grey	7	560.16876	560.32876	562.16876	562.32876
	50/60	(3) 600-690	Black	5	560.16877	560.32877	562.16877	562.32877
	60	440-460	Red	11	560.16875	560.32875	562.16875	562.32875
	50/60	380/220	Red	3	560.16874	560.32874	562.16874	562.32874
	>300-500	(1) >50	Green	2	560.16872	560.32872	562.16872	562.32872

16A M25 h 1/4	32A M25 h 1/4
567.1670	567.3270
567.1683	567.3283
567.1678	567.3278
567.16836	567.32836
567.16833	567.32833
567.16832	567.32832
567.16834	567.32834
567.16838	567.32838
567.1672	567.3272
567.1674	567.3274
567.1686	567.3286
567.16865	567.32865
567.16866	567.32866
567.16867	567.32867
567.16864	567.32864
567.16861	567.32861
567.16862	567.32862
567.1679	567.3279
567.1675	567.3275
567.1687	567.3287
567.16876	567.32876
567.16877	567.32877
567.16875	567.32875
567.16874	567.32874
567.16872	567.32872



#### Rated voltage >50V

- Approvals: from page 181
- Switches as spare parts: page 188
- Supplied with stainless steel fixing screws.

(1) The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging

above 100 Hz; contact Scame Technical Service for further information.

(2) When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

(3) Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.

#### ADVANCE2 System

From page 110

