

### ■ WITHOUT BASE - IP66/IP67 - WITHOUT FUSE HOLDER

ADVANCE-GRP Series

402.



403.



I-DEVICE

| Poles  | Hz              | Volt              | Colour | h. | 16A       |           |           | 32A |     |     | 63A |     |     |     |
|--------|-----------------|-------------------|--------|----|-----------|-----------|-----------|-----|-----|-----|-----|-----|-----|-----|
|        |                 |                   |        |    | □ 1       | □ 1       | □ 1       | □ 1 | □ 1 | □ 1 | □ 1 | □ 1 | □ 1 | □ 1 |
| 2P+E   | 50/60           | 100-130           |        | 4  | 402.1670  | 402.3270  | 402.6370  |     |     |     |     |     |     |     |
|        | 50/60           | 200-250           |        | 6  | 402.1683  | 402.3283  | 402.6383  |     |     |     |     |     |     |     |
|        | 50/60           | 380-415           |        | 9  | 402.1678  | 402.3278  | 402.6378  |     |     |     |     |     |     |     |
|        | 50/60           | 480-500           |        | 7  | 402.16836 | 402.32836 | 402.63836 |     |     |     |     |     |     |     |
|        | 50/60           | trasf.            |        | 12 | 402.16833 | 402.32833 | 402.63833 |     |     |     |     |     |     |     |
|        | >300-500        | (1) >50           |        | 2  | 402.16832 | 402.32832 | 402.63832 |     |     |     |     |     |     |     |
|        | c.c.            | (2) >50-250       |        | 3  |           |           |           |     |     |     |     |     |     |     |
|        | c.c.            | (2) >250          |        | 8  |           |           |           |     |     |     |     |     |     |     |
| 3P+E   | 50/60           | 100-130           |        | 4  | 402.1672  | 402.3272  | 402.6372  |     |     |     |     |     |     |     |
|        | 50/60           | 200-250           |        | 9  | 402.1674  | 402.3274  | 402.6374  |     |     |     |     |     |     |     |
|        | 50/60           | 380-415           |        | 6  | 402.1686  | 402.3286  | 402.6386  |     |     |     |     |     |     |     |
|        | 60              | 440-480           |        | 11 | 402.16865 | 402.32865 | 402.63865 |     |     |     |     |     |     |     |
|        | 50/60           | 480-500           |        | 7  | 402.16866 | 402.32866 | 402.63866 |     |     |     |     |     |     |     |
|        | 50/60           | (3) 600-690       |        | 5  | 402.16867 | 402.32867 | 402.63867 |     |     |     |     |     |     |     |
|        | $\frac{50}{60}$ | $\frac{380}{415}$ |        | 3  | 402.16864 | 402.32864 | 402.63864 |     |     |     |     |     |     |     |
|        | 100-300         | (1) >50           |        | 10 | 402.16861 | 402.32861 | 402.63861 |     |     |     |     |     |     |     |
|        | >300-500        | (1) >50           |        | 2  | 402.16862 | 402.32862 | 402.63862 |     |     |     |     |     |     |     |
|        | 50/60           | 100-130           |        | 4  | 402.1679  | 402.3279  | 402.6379  |     |     |     |     |     |     |     |
| 3P+N+E | 50/60           | 208-250           |        | 9  | 402.1675  | 402.3275  | 402.6375  |     |     |     |     |     |     |     |
|        | 50/60           | 346-415           |        | 6  | 402.1687  | 402.3287  | 402.6387  |     |     |     |     |     |     |     |
|        | 50/60           | 480-500           |        | 7  | 402.16876 | 402.32876 | 402.63876 |     |     |     |     |     |     |     |
|        | 50/60           | (3) 600-690       |        | 5  | 402.16877 | 402.32877 | 402.63877 |     |     |     |     |     |     |     |
|        | 60              | 440-480           |        | 11 | 402.16875 | 402.32875 | 402.63875 |     |     |     |     |     |     |     |
|        | $\frac{50}{60}$ | $\frac{380}{415}$ |        | 3  | 402.16874 | 402.32874 | 402.63874 |     |     |     |     |     |     |     |
|        | >300-500        | (1) >50           |        | 2  | 402.16872 | 402.32872 | 402.63872 |     |     |     |     |     |     |     |

| I-DEVICE   |            |            |
|------------|------------|------------|
| 16A        | 32A        | 63A        |
| □ 1        | □ 1        | □ 1        |
| 403.1670   | 403.3270   | 403.6370   |
| 403.1683   | 403.3283   | 403.6383   |
| 403.1678   | 403.3278   | 403.6378   |
| 403.16836  | 403.32836  | 403.63836  |
| 403.16833  | 403.32833  | 403.63833  |
| on request | on request | on request |
| 403.1672   | 403.3272   | 403.6372   |
| 403.1674   | 403.3274   | 403.6374   |
| 403.1686   | 403.3286   | 403.6386   |
| 403.16865  | 403.32865  | 403.63865  |
| 403.16866  | 403.32866  | 403.63866  |
| 403.16867  | 403.32867  | 403.63867  |
| 403.16864  | 403.32864  | 403.63864  |
| on request | on request | on request |
| on request | on request | on request |
| 403.1679   | 403.3279   | 403.6379   |
| 403.1675   | 403.3275   | 403.6375   |
| 403.1687   | 403.3287   | 403.6387   |
| 403.16876  | 403.32876  | 403.63876  |
| 403.16877  | 403.32877  | 403.63877  |
| 403.16875  | 403.32875  | 403.63875  |
| 403.16874  | 403.32874  | 403.63874  |
| on request | on request | on request |



#### Rated voltage >50V

- Approvals: from page 561
- Switches as spare parts: page 189
- Supplied with stainless steel fixing screws.

(1) The maximum amount of current available, taking into account the maximum overheating temperature allowed by the relevant standards, must be downgraded with respect to the nominal current by 25% for products with frequencies ranging

above 100 Hz; contact Scame Technical Service for further information.

(2) When using DC we recommend that you make sure of implementing the protection scheme that is most suitable for the system involved; contact Scame Technical Service for further information.

(3) Pay special attention when selecting the appropriate fuse with respect to the tension of the installation.



ADVANCE-GRP System  
From page 122