

IEC309 Series

OPTIMA Series

210.



213.



Poles	Hz.	Volt	Colour	h.	IEC309 Series		OPTIMA Series		FAST WIRING	
					16A cable sleeve Ø 10/100	32A cable sleeve Ø 10/100	16A cable gland Ø 10/50	32A cable gland Ø 10/40	16A cable gland Ø 10/50	32A cable gland Ø 10/40
2P+E	50/60	100-130		4	210.1630		213.1630 (Δ)	213.3230	213.1630P (Δ)	213.3230F
	50/60	200-250		6	210.1633	210.3233	213.1633 (▲) (Δ)	213.3233 (▲)	213.1633P (▲) (Δ)	213.3233F (▲)
	50/60	380-415		9			213.1638	213.3238	213.1638P	213.3238F
	50/60	480-500		7			213.16336	213.32336		
	50/60	trasf.		12			213.16333	213.32333		
	>300-500	>50		2			213.16332	213.32332		
	c.c.	>50-250		3			213.16334	213.32334		
	c.c.	>250		8			213.16338	213.32338		
3P+E	50/60	100-130		4			213.1631	213.3231		
	50/60	200-250		9	210.1634	210.3234	213.1634	213.3234	213.1634P	213.3234F
	50/60	380-415		6	210.1636	210.3236	213.1636 (▲) (•)	213.3236 (▲) (•)	213.1636P (▲) (Δ)	213.3236F (▲)
	60	440-460		11			213.16365	213.32365		
	50/60	480-500		7			213.16366	213.32366		
	50/60	600-690		5			213.16367	213.32367		
	50/60	380/440		3			213.16364	213.32364		
	100-300	>50		10			213.16361	213.32361		
3P+N+E	>300-500	>50		2			213.16362	213.32362		
	50/60	100-130		4			213.16362	213.32362		
	50/60	208-250		9			213.1632	213.3232		
	50/60	346-415		6			213.1635	213.3235		
	50/60	480-500		7	210.1637	210.3237	213.1637 (▲) (•)	213.3237 (▲) (•)	213.1637P (▲) (Δ)	213.3237F (▲)
	50/60	600-690		5			213.16376	213.32376		
	60	440-460		11			213.16377	213.32377		
	50/60	380/440		3			213.16375	213.32375		
>300-500	>50		2			213.16374	213.32374			
							213.16372	213.32372		



(•) Phase inverter
Plugs and flush mounting
appliance inlets with phase
inverter, page 44



(▲) Black-coloured
Versions also available in black;
just add ".K" at the end of the
catalogue number.
Example 213.1633.K



(Δ) Transparent grip
Version also available with
transparent grip; just add ".TR"
at the end of the catalogue
number. Example 211.1633.TR