




# ADAPTO System - IP66

## surface mounting enclosure

### ■ EMPTY CASING - IP66

ADAPTO Series

Description	Installation	⊞		 (*)	 (*)
Casing for 4-way adaptors	Portable or suspended (PG21)	1/4		⊞ 623.4500-000	
	Elevated installation	1/4		⊞ 625.4500-000	
Casing for 3-way adaptors and protection devices (6 DIN)	Portable or suspended (PG21)	1/4			⊞ 623.3500-000
	Elevated installation	1/4			⊞ 625.3500-000

- Protection degree max. IP66 depending on the socket outlets installed.
- Staffe di supporto in acciaio zincato.
- Completi di fermacavo.

(\*) Opening suitable for SCAME industrial 16A socket outlets (flange 70x87 mm) 32A socket outlets (flange 84x106 mm) and socket outlets for domestic application (flange 70x87 mm).

### ■ PLATE FOR PANEL CUT-OUTS




ACCESSORIES

Flange	⊞				
70x87	25	654.0100	654.0101(*)	654.0101Y(*)	654.0102(*)

(\*) For components TOP22 Series.

### ■ ADAPTO KIT ACCESSORIES

ACCESSORIES

Description	⊞			
Tubular stand kit	Zinc-plated steel tubular stand (Ø80 h 1000mm) with earthing bolt. For 3 and 4-way adaptors. Fixing flanges: - upper 120x90mm - lower 220x220mm	1	692.4340	
	Aluminium steel plate for compressed air chosed attachment. Flange 50x60mm. For 2, 3 and 5-way adaptors.	1		654.0050
Adaptors coupling kit	5			692.4342