

Emergency call points

■ FLUSH MOUNTING VERSION - IP55

EMERGENCY
Series



Description	Dimension (mm)	⊞	
With push button and hammer	100x100x50mm	1/13	676.25100

- Can be mounted in flush mounting box with centre-to-centre distance 83.5 mm.
- With illuminated push button (24V incandescent or 250V fluorescent bayonet lamp - 12V).
- With 1 NO contact and 1 NC contact (2A, 250V).
- Complete with glass-breaking hammer.

■ SURFACE MOUNTING VERSION - IP55

EMERGENCY
Series



Description	Dimension (mm)	⊞	
With push button and hammer	100x100x50mm	1/14	676.35100

- With illuminated push button (24V incandescent or 250V fluorescent bayonet lamp - 12V).
- With 1 NO contact and 1 NC contact (2A, 250V).
- Complete with glass-breaking hammer.

■ SURFACE MOUNTING VERSION - IP65

EMERGENCY
Series



Description	Dimension (mm)	⊞	
With push button and hammer	100x100x50mm	1/14	676.35100

- With illuminated push button (24V incandescent or 250V fluorescent bayonet lamp - 12V).
- With 1 NO contact and 1 NC contact (2A, 250V).
- Complete with glass-breaking hammer.

■ SURFACE MOUNTING VERSION - IP65

EMERGENCY
Series



Description	Dimension (mm)	⊞	
With DIN rail (6 modules)	205x220x140mm	1/6	676.35201
With mounting plate	205x220x140mm	1/6	676.35205

- Equipped with flange to facilitate junctions.