

Aluminium junction boxes

ENCLOSURES - IP66

ALUBOX Series

ALUBOX-EX Series



Dimensions (mm)		Screw for attaching cover	Earthing screws	Weight (Kg)	⊞		
100x100x59	⊞	n° 2 M5x10mm	n°1 M4x6	0,255	1/32	653.00	653.9000
140x115x60	⊞	n° 4 M5x16mm	n°1 M4x6	0,400	1/24	653.01	653.9001
166x142x64	⊞	n°4 M5x16mm	n°1 M4x6	0,585	1/16	653.02	653.9002
192x168x80	⊞	n° 4 M5x16mm	n°1 M4x6	0,870	1/12	653.03	653.9003
253x217x93	⊞	n° 4 M6x20mm	n°1 M4x6	1,760	1/6	653.04	653.9004
314x264x122	⊞	n° 4 M6x20mm	n°1 M4x6	2,880	1/2	653.05	653.9005
410x315x153	⊞	n° 4 M6x20mm	n°1 M4x6	6,500	1	653.07	653.9007

- Enclosure and cover in die-cast aluminium.

- Externally varnished.

- With stainless steel screws for attaching cover and self-tapping zinc-coated steel screws for earthing the enclosure and cover.

⊞ = counter-sunk head screw.

⊞ = flat head screw.



Enclosures and covers in aluminium alloy with blank walls and covered.



Holding seal in expanded EPDM, already mounted in place on the cover



Fixing to wall by brackets incorporated in the enclosure base