



AVAILABLE 16A SOCKET OUTLET			AVAILABLE 32A SOCKET OUTLET		POWER SUPPLY	WITH CABLE AND PLUG		WITH APPLIANCE INLET	
2P+E	3P+E	3P+N+E	3P+E	3P+N+E	Plug	IP44 ☒ 1/6	IP66 ☒ 1/6	IP44 ☒ 1/6	IP66 ☒ 1/6
2					16A 2P+E 6h	604.1623/C	605.1623/C	600.1623	601.1623
	2				16A 3P+E 6h	604.1626/C	605.1626/C	600.1626	601.1626
	2				16A 3P+E 6h			600.1626/l (*)	
		2			16A 3P+N+E 6h		605.1627/C	600.1627	601.1627
1	1				16A 3P+N+E 6h	604.1629/C		600.1629	601.1629
			2		32A 3P+E 6h	604.3226/C	605.3226/C		
				2	32A 3P+N+E 6h	604.3227/C	605.3227/C		

(\*) 1 socket with reversed phases.



A mechanical retaining device (catch), as required by EN60309 standard, is found on the body of the adaptor.



A small hole allows the adaptor to be suspended.

**2-way adaptors**

- Casing provided with lug for hanging from above (16A).
- Zinc-plated steel carrying handle (32A).
- Equipped with PG21 cable gland, cable clamp and terminal block.
- 2m of H07RN-F rubber cable.