

Cable reels with automatic rewind

WITH H05VV-F PVC CABLE - IP41

AUTOROLLER Series



POWER SUPPLY		MAX LOAD (W)			
Cable					
	Type	Metres	e_{\perp}	Q_{\perp}	\varnothing
2 poles	2x1	16	1100	1400	1
	2x1,5	12	1500	2100	1
	2x2,5	10	2000	2300	1
3 poles (2P+E)	3x1	14	1000	1400	1
	3x1,5	12	1500	2100	1
	3x2,5	8	2300	2300	1

- H05VV-F PVC cable.

WITH DOMESTIC PLUG AND TRAILING SOCKET FOR DOMESTIC APPLICATION - IP40

AUTOROLLER Series



POWER SUPPLY		MAX LOAD (W)			
Cable					
	Type	Metres	e_{\perp}	Q_{\perp}	\varnothing
	3x1,5	12	1500	2100	1

- H05VV-F PVC cable.
- Plug: Italian standard 250V~ - 2P+E 16A Ⓞ
- Trailing socket: Italian standard 220V~ - 2P+E - 16A - Dual use Ⓞ

Warning: AUTOROLLER Series cable reels must be protected against overcurrents by appropriate devices installed upstream and with a rated current not exceeding that indicated in the table.

WITH PLUG AND PORTABLE LAMP - IP20

AUTOROLLER Series



Cable	Transformer	Max current wound (*)	Max load wound	\varnothing
16m 2x1mm ²	without transformer	4A	60W - 230V~	1
16m 2x1mm ²	230/12-24V~	2,5A (fus.)	60W - 12-24V~	1

(*) Without thermal overload switch.
- H05VV-F PVC cable.
- Plug: Italian standard 250 V~ - 2P - 10A ⓄBLUELINE Series.
- Lampholder E27.

- Max. bulb 60 W.
- SELV transformer 60VA 50 Hz Ⓞ
- Protection on the transformer secondary: thermal overload switch.

WITH PLUG AND PORTABLE LAMP - IP40

AUTOROLLER Series



Cable	Transformer	Max load wound	\varnothing
14m 2x1mm ²	230/12-24V~	60W	1

- H07RN-F cable.
- Plug: IEC 309 standard 250 V~ - 2P+E 16A Ⓞ
- Lampholder E27.

- Max. bulb 60 W.
- SELV Transformer 60 VA - 50 Hz Ⓞ
- Protection on the transformer secondary: thermal overload switch.

PORTABLE HEAVY DUTY LAMP

HALE Series



Description	Lampholder	\varnothing
Without cable and plug	E27	1

- Black color.

Note

This is just a small selection of our full range. Please contact your SCAME dealer for versions with other industrial or domestic socket outlets (Italian, German, British or French standard).