

Cable reels for industrial applications

WITH 4 SOCKET AND THERMAL OVERLOAD SWITCH

ROLLER450 Series



AVAILABLE SOCKETS			POWER SUPPLY			MAXLOAD (W)		IP44		IP55	
2P+E	3P+E	3P+N+E	Plug 16A	Cable		⌀	⌀	Volt. (V-)	⏏		
				Type	Metres						
4			2P+E	3x2,5	30	1800	3600	230	1	745.3005-012	745.3505-012
4			2P+E	3x2,5	50	1600	3600	230	1	745.5005-012	745.5505-012
	4		3P+E	4x2,5	30	4500	11000	400	1	745.3005-013	745.3505-013
	4		3P+E	4x2,5	50	4000	11000	400	1	745.5005-013	745.5505-013
		4	3P+N+E	5x2,5	30	5000	11000	400	1	745.3005-096	745.3505-096
		4	3P+N+E	5x2,5	50	4000	11000	400	1	745.5005-096	745.5505-096
2	2		3P+N+E	5x2,5	30	5000	11000	400	1	745.3005-003	745.3505-003
2	2		3P+N+E	5x2,5	50	4000	11000	400	1	745.5005-003	745.5505-003
2		2	3P+N+E	5x2,5	30	5000	11000	400	1	745.3005-006	745.3505-006
2		2	3P+N+E	5x2,5	50	4000	11000	400	1	745.5005-006	745.5505-006
3	1		3P+N+E	5x2,5	30	5000	11000	400	1	745.3005-008	745.3505-008
3	1		3P+N+E	5x2,5	50	4000	11000	400	1	745.5005-008	745.5505-008
3		1	3P+N+E	5x2,5	30	5000	11000	400	1	745.3005-094	745.3505-094
3		1	3P+N+E	5x2,5	50	4000	11000	400	1	745.5005-094	745.5505-094

- On demand available with 32A sockets.

Cable reels for industrial applications:

- Cable H07RN-F (RUBBER).
- The maximum connectable load is shown on each item.