

















































Insulated wire connectors

INSULATED WIRE CONNECTORS T85 - SINGLE



Connecting capacity (mm ²)	Rated current (A)	Colour	□	
1,5	17,5		100/600	 810.372/V
			100/600	 810.372/N
			100/600	 810.372/B
			100/600	 810.372/M
			100/600	 810.372/G
		Transparent	100/600	 810.372/TR
		Assorted (*)	100/600	 810.372/AS
2,5	24		100/1000	 810.374/V
			100/1000	 810.374/N
			100/1000	 810.374/B
			100/1000	 810.374/M
			100/1000	 810.374/G
		Transparent	100/1000	 810.374/TR
		Assorted (*)	100/1000	 810.374/AS
4	32		100/1000	 810.375/V
			100/1000	 810.375/N
			100/1000	 810.375/B
			100/1000	 810.375/M
			100/1000	 810.375/G
		Transparent	100/1000	 810.375/TR
		Assorted (*)	100/1000	 810.375/AS
6	41		100/1000	 810.376/V
			100/1000	 810.376/N
			100/1000	 810.376/B
			100/1000	 810.376/M
			100/1000	 810.376/G
		Transparent	100/1000	 810.376/TR
		Assorted (*)	100/1000	 810.376/AS

(*) Transparent excluded